

Wednesday, September 17, 2008



[Signs, Banners, Engraving & Digital Printing](#)
FAST & On Time Every Time!
Not Sometimes...

[Home](#) || [Products](#) || [Order Online](#) || [Price Quote](#) || [Request Information](#) || [Contact us](#)

Quality Care and Use of Your Magnetic Sign

1. The holding power of your magnetic sign is 85 pounds per square foot.
2. The magnetic material of your sign will stay flexible from -10 degrees Fahrenheit to + 160 degrees Fahrenheit.
3. Both the vehicle surface and the brown magnetic side of the sign should be clean, dry, and waxed prior to applying.
4. To apply your magnetic sign let one edge of the sign contact the vehicle in the desired position. Then, let the magnetic power do the work as it puts the sign into place from the edge where you started to the edge opposite. If the sign is not exactly where you want it, peel it off, reposition the starting edge and repeat. Make sure that the entire surface of the sign is smoothly against the vehicle with no air pockets underneath. In winter the temperature of the sign should be about 50 degrees F during installation, but the temperature of the vehicle surface does not matter.
5. Remove the sign weekly and wipe dry both the magnetic side and the surface of the vehicle. This keeps moisture from collecting, which can potentially damage a vehicle's surface. Cleaning the display side of a magnetic sign is just as easy. Simply wash it with warm water and mild detergent.
6. When storing your sign avoid wrinkling by rolling it in a 3 inch diameter roll with printed side of the sign pointed to the outside of the roll, or store the sign flat. Do not put heavy things on or against the sign in storage.

[Home](#) || [Products](#) || [Order Online](#) || [Price Quote](#) || [Request Information](#) || [Contact us](#)